List of Figures

Figure III.A-1. 47-State Light-Duty NOx Emissions Without Tier 2/Sulfur
(Annualized Summer Tons)
Figure III.A-2. Breakdown of Total 2030 47 State NOx Inventory Without Tier 2 III-
Figure III.A-3. Breakdown of Total 2030 Atlanta NOx Inventory Without Tier 2 III-
Figure III.A-4. 47-State Light-Duty NOx Emissions With Tier 2/Sulfur
(Annualized Summer Tons)
Figure III.A-5. Breakdown of Total 2030 47-State NOx Inventory With Tier 2/Sulfur III-1
Figure III.A-6. Breakdown of Total 2030 Atlanta NOx Inventory With Tier 2/Sulfur III-1-
Figure III.A-7. 47-State Light-Duty VOC Emissions Without Tier 2/Sulfur
(Annualized Summer Tons)
Figure III.A-8. Breakdown of Total 2030 47-State VOC Inventory Without Tier 2/Sulfur
III-2
Figure III.A-9. Breakdown of Total 2030 Atlanta VOC Inventory Without Tier 2/Sulfur III-2
Figure III.A-10. 47-State Light-Duty VOC Emissions With Tier 2/Sulfur
(Annualized Summer Tons)
Figure III.A11. Breakdown of Total 2030 47-State VOC Inventory With Tier 2/Sulfur III-2.
Figure III.A-12. Breakdown of Total 2030 Atlanta VOC Inventory With Tier 2/Sulfur III-2.
Figure III.A-13. 47-State Light-Duty SOx Emissions Without Sulfur Control
(Annual Tons)
Figure III.A-14. 47-State Light-Duty SOx Emissions With Sulfur Control
(Annual Tons) III-3
Figure III.A-15. 47-State Light-Duty Direct Exhaust PM ₁₀ Emissions
Without Tier 2/Sulfur - No Diesel Growth (Annual Tons) III-3:
Figure III.A-16. 47-State Light-Duty Direct Exhaust PM ₁₀ Emissions With Tier 2/Sulfur - No
Diesel Growth (Annual Tons) III-3
Figure III.A-17: 47-State Light-Duty Direct Exhaust PM ₁₀ Without Tier 2/Sulfur - Increased
Diesel Sales (Annual Tons)
Figure III.D-1. Example Plot of Target Fuel Benzene Versus
Baseline Fuel TOG under FTP Conditions III-9
Figure IV-1. Impact of Coating Architecture on HC and NOx Emissions IV-1
Figure IV-2: 50,000 mile equivalent NOx vs. NMHC levels for a number of hardware and engine
calibration configurations tested with a 1999 GM Chevrolet Silverado Pickup (5.3L V8)
originally certified to the LEV MDV-2 standard (0.4 g/mi NOx, 0.16 g/mi NMOG). IV-3
Figure IV-3: 50,000 mile equivalent NOx vs. NMHC emissions levels for a number of hardware
and engine calibration configurations tested with a 1999 Ford Expedition (5.4L V8)
originally certified to the LEV MDV-3 standard (0.6 g/mi NOx, 0.195 g/mi NMOG)
Figure IV-4. Map of U.S. Petroleum Administrative Districts for Defense IV-4
Figure IV-5. Diagram of a Typical Complex Refinery

Tier 2/Sulfur Regulator	y Impact Analy	ysis - December	1999
-------------------------	----------------	-----------------	------

Figure V-1.	Distribution of Progress Ratios	V-25
Figure V-2.	Total Annualized Costs of Tier 2 Vehicles and Low Sulfur Gasoline	V-91